Garage/Workshop Fire Extinguisher

Part number 21005766N | **Garage/Workshop use** | **Single use**

UL Rated 3-A, 40-B:C

Meets NFPA recommendations for the garage and workshop

For use on the following types of fire:

Description

Due to the volume of flammable liquids normally present in garages & workshops a higher rated fire extinguisher is recommended.

Fights fires common to the garage and workshop such as paint, wood, gasoline & energized electrical equipment. This unit is easy to use and has a 10 year warranty.

Includes plastic wall hanger (293263).

At a Glance

- Model FX340GW
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 10 year limited warranty

Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 5.5 lb. of fire extinguishing agent (Average)
- 10 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection

Pt # 21005766N- 4 pack
UPC: 0-47871-05766-5
I2F - 10047871057662

Product Specification

Net agent weight (Average)	5.5 lb.
Unit weight (Average)	8.25 lb.
Diameter	4.5 inches
Height	16.8 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Wall hanger	UL Listed

Packaging Options

Master Pack (4)	21005766N

Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	17.0
Pack (4)	13	17.5	10

Kidde
United Technologies

Kidde Fire Safety
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com